



GRANGE WORKS, GRANGE ROAD
BATLEY, WEST YORKSHIRE, WF17 6LN



WWW.RELIANTRUBBER.CO.UK



01924 420098



INFO@RELIANTRUBBER.CO.UK



NBR/SBR NITRILE



Nitrile Rubber sheeting is a synthetic rubber created for applications where it meets petroleum-based products, oils, fats, and greases. Nitrile displays good mechanical strength within a moderate temperature range and is used widely within the Automotive and Aerospace industries.

Nitrile can be compounded for use in the food and drink industry.


Nitrile produces excellent gaskets, O-rings, oil seals, transmission belts and hoses.



FULL ROLLS



CUT TO LENGTHS



BESPOKE GASKET

For additional details, please scan the QR code, which will direct you straight to our website.





RELIANT RUBBER 

@RELIANTRUBBER 






RELIANT RUBBER 

RELIANT RUBBER ENGINEERS LIMITED 

NBR/SBR NITRILE

FULL ROLL DIMENSIONS	10M LONG X 1.2M WIDE	
GRADE	COMMERCIAL	
COLOUR	BLACK	
SURFACE FINISH	SMOOTH/SMOOTH	
HARDNESS, SHORE A	65+/-5	ISO 7619-1
ABRASION RESISTANCE	ABOVE AVERAGE	
ELONGATION AT BREAK %	250	ISO 37
TENSILE STRENGTH	4MPA	
TEMPERATURE RANGE	-20 TO +80 C	

CHEMICAL RESISTANCE

WATER	OZONE	ACIDS	SOLVENTS	OILS	
					EXCELLENT
					ABOVE AVERAGE
					AVERAGE
					BELOW AVERAGE
					POOR